Technical specification

- Size: 25X20X23cm
- Weight: 1.5kg/pcs without canister
- Display: Colorful Touch Screen
- Maximum Vacuum: -335mmHg
- Treatment modes: Continuous Therapy, Dynamic Therapy, Intermittent Therapy
- Pressure Value: -50mmHg -335mmHg
- Free Air Flow Rate: Less 20L/Min
- Quiet treatment: <60dB
- Alarm indicator: Blockage, Leakage, Low battery alarm
- Battery operation time: more than 3 hours
- Charge time: 3 hours
- Connected electrical power: Input AC 100-240VAC, Output DC18V, 2A.
- Accessory Canister: 1000ml and 2000ml



Indications for Use :
It is indicated for patients who would benefit from a suction device (negative pressure wound therapy) as it may promote wound healing via removal of low to moderate levels of exudate and infectious materials.
welsuc negative pressure wound therapy system is suitable for use both in a hospital and homecare setting.

Scope of Application : suitable for Acute & Chronic wounds, diabetic foot ulcers, venous ulcers,bedsores, neuropathic ulcers, donor sites, omphalocele, post-operative abdominoplasty, etc.

Negative pressure wound therapy dressing



Application:Acute&Chronic wounds,diabetic foot ulcers,venous ulcers,bedsores,neuropathic ulcers,donor sites,omphalocele,post-operative abdominoplasty,etc.

No.	Item Name	Item No.	Specification	Including accessories	Classification	Shelf life	Sterile
1	NPWT dressing	C.JE.WM.10073B	10X7X3cm	Black foam, tube with the pad, adhesive film, I/Y connector, clip	Class II	2 Years	Yes
2	NPWT dressing	C.JE.WM.15103B	15X10X3cm	Black foam, tube with the pad, adhesive film, I/Y connector, clip	Class II	2 Years	Yes
3	NPWT dressing	C.JE.WM.20103B	20X10X3cm	Black foam, tube with the pad, adhesive film, I/Y connector, clip	Class II	2 Years	Yes
4	NPWT dressing	C.JE.WM.25153B	25X15X3cm	Black foam, tube with the pad, adhesive film, I/Y connector, clip	Class II	2 Years	Yes
5	NPWT dressing	C.JE.WM.30203B	30X20X3cm	Black foam, tube with the pad, adhesive film, I/Y connector, clip	Class II	2 Years	Yes